



Pergotenda® Kubo



An aluminum modular Pergotenda® that includes all the bells and whistles. The Kubo can be either freestanding or wall mounted as well as linked together with other Kubos, making it easy to cover large spaces.

Time to come together



Making Connections

Pergotenda® Kubo (2 top left) | Outdoor Living Solutions, London ON Canada

Pergotenda® Kubo with custom yellow frame color | Total Shade, Frisco TX



Holiday Inn | Rome, Italy

Piazza | Knokke-Heist, Belgium

PERGOTENDA® KUBO



Kubo is a retractable, self-supporting or wall mounted cover system custom made to protect against sun and rain. It consists of an aluminum structure and a folding canvas. The fabric is supported by intermediate supporting tubes (1.6"x2") and terminal bars (3.2"x2") set parallel to one another every 20" approximately. The canvas moves by sliding on the runners (2"x3.5") on carriers with 6 asymmetrical wheels with a capacity of about 1000 lbs each. The toothed transmission belt has stainless steel cables and resists a saline environment; the tensile strength is of 2000 lbs at break; the transmission belt is inserted in each runner, controlled by the drive pulley and a single drive shaft that guarantees the smooth movement of the canvas. The KUBO system is operated by a radio-controlled Dunker D839 motor. Aluminum tubular structure 4.8"x4.8". Perimeter paneling is 0.2" thick, white opal methacrylate. Hardware and accessories are 304 stainless steel. While Corradi USA possesses a great deal of data related to engineering for the Pergotenda® product line that is related to wind ratings and load data that has been developed through specific product tests, case studies and IBC testing. It is understood that when required and due to the custom nature of our projects, engineering must be project specific and adhere to the rules and regulations at the local level where such a project shall be planned and installed.

FEATURES

ANTIDRIP SYSTEM Weldable PVC profile on the upper part of the canvas for lateral rainwater retention. This PVC profile is welded to each far side of a pitched roof canopy to prevent water from dripping over the sides and forces the water to shed into the gutter system.

ANTISPRAY PROFILE PVC profile inserted on the lateral side of the runner for retention of rainwater spray. Always in addition to the ANTIDRIP SYSTEM. The AntiSpray prevents water from a heavy downpour from "splashing" over the AntiDrip profile and dripping over the sides.

FLAT ONLY The Kubo is only available flat.

MODULAR System modules can be connected for exponentially greater coverage.

MOTORIZATION All Pergotenda® are motorized, giving you complete control at the touch of a button.

HOOD The Protective Hood Cover is an aluminum corrugated standing seam cover that is positioned where the unit mounts to the wall or at the back of the unit on a Freestanding model for the purpose of protecting the Roof Canopy Swags that created when the roof retracts and to prevent any water or debris from collecting in the swags. The Protective Hood Cover is powder coated for longevity.

OPTIONS

ADD-ON INTERMEDIATE SUPPORT TUBE Used to reduce the height of the canopy swag when the roof unit is retracted, usually for purposes of clearing a door opening or a window. Only two (2) tubes total may be added to any single roof canopy.

ADD-ON RUNNER The mechanical Runner is the equivalent of roof truss or rafter and is what the roof canopy is attached to. The Kubo may have up to a maximum of 4 runners.

FAUX CEILING A unique option that hangs a colorful fabric beneath the roofing material to add warmth and atmosphere to the room. The Faux Ceiling fabric can provide for an excellent opportunity to blend other colors or materials that are part of furnishings or cushions. The softer fabric material may also be a benefit in reducing noise or providing other minimal acoustic properties to dampen surrounding noise. This option will depend on the type of fabric. The Faux Ceiling fabric generally must be from the Corradi USA collection or an approved alternate.

GABLE (pitched versions only) A fixed fabric portion used to enclose the angled gap on both sides of a pitched system when using screens.

LIGHTING The Pergotenda® lighting system is a custom designed system that seamlessly integrates into the Pergotenda® intermediate tubes.

RETRACTABLE GUTTER Extruded aluminum profile for rainwater collection, only for pitched versions, fixed to the end support tube. One drainage per runner. Down pipes not provided. The gutters moves with the roof canopy and has downspouts that merge into a CNC cut in each front supporting post.

STRATUS SCREEN An exterior screen specifically designed to integrate into most Pergotenda® systems for complete enclosure that assists in protection from the elements and gives the option of privacy.

TRAPEZOIDAL FABRIC (flat versions only) An alternative drainage option for flat systems to let you control which side of the system you want rain to fall off.


UNDERSIDE DRIP-COLLECTION RIM (flat versions only) Welded PVC profile on the underside of the roof canopy to channel water into the side gutters and to prevent water from running along the underside of the roof canopy and dripping down.

FREESTANDING OR WALL MOUNT Can be attached to wall or self supporting.

FRAME COLORS

POWDER COATING*

The aluminum extrusions are painted with certified Qualicoat cycle epoxy powders. The support tubes come in: White Quartz, Glacier, & Beach Sand to match with the Eclissi fabric.



WHITE QUARTZ




ANTHRACITE




CARBON



GLACIER



BEACH SAND




DUNE



GRANITE



CORTEN




URBAN BRONZE

*RAL CUSTOM COLOR POWDER COATING IS ALSO AVAILABLE
Due to print variation these finish images should not be used for final production specifications.

FABRICS

ECLISSI BLACKOUT FABRIC

Eclissi fabric is exclusively used by Corradi USA for Pergotenda® structures. It is a High tenacity 1100 Dtex Polyester base fabric with PVC laminate. The embossed finish on the inner side gives a textile appearance and a dynamic weft effect on the viewable surface. The outer side has an anti-dust acrylic lacquer. This unique 4-ply material has a blackout layer that also acts as a radiant barrier, providing superior heat resistance and heat gain as compared to other textiles used in these types of applications. It is available in 3 colors:



ECLISSI WHITE



ECLISSI GREY



ECLISSI IVORY

OTHER RETRACTABLE ROOF FABRICS AVAILABLE

SERGE FERRARI SOLTIS PROOF W96

See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS PROOF 502

See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS PERFORM 92



See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS HORIZON 86

See Fabrics section pg. 155 for more information on this fabric.

MOTORS

RADIO CONTROLLED DUNKER D839



	FLAT MAX DIMENSIONS STANDARD slack	
	Width	Projection
2 runner	138"	236"
3 runner	276"	236"
4 runner	413"	236"

	FLAT MAX DIMENSIONS TRAPEZOIDAL slack	
	Width	Projection
2 runner	197"	236"
3 runner	315"	236"
4 runner	472"	236"